



**AusPress®**

**FLOOR GULLY**

HACCP INTERNATIONAL  
PROGRAMME  
CERTIFICATION



**WaterMark**  
AS 3495  
Certificate No. 687




**Installed quickly & easily, the Floor Gully range has the advantage when hygiene, high temperatures and performance are critical.**



Partnering  
with ACO



High  
Load  
Ratings



High  
Temp  
Suitable



Hygienic  
Design

## Hygienic Performance

- Self-draining internal design to prevent stagnant water pooling.
- Concrete, tiled, epoxy and vinyl sheet floor type suitable.
- Epoxy edge lip infill for strength and hygiene.
- HACCP & EHEDG approved.
- Removable internal components for easier cleaning.

## Experience Counts

- We were the first to supply stainless drainage in Australia and New Zealand.
- We work with consultants and installers on specialised complex projects regularly.
- In-house design staff with local fabrication available for project requirements.

## Quality to Install

- Square, round and vinyl lock top designs available & stocked.
- Approved to WaterMark, Australian and international standards.
- Easy adjust support legs standard with stabilising feet.
- Designed specifically for hygiene and easy cleaning.

## Reliable Design

- With the strength and chemical resistance qualities of stainless steel.
- Range of grate options for pedestrian, forklift and truck load requirements.

## Environmental Choice

- Long service life.
- Closed loop material (completely recycled to make more stainless).

# Specification Guide

AusPress supply the Floor Gully range as individual components where depending on the application, the selected accessories are designed to fit within the drain bowl.

Accessories include the grate type, filter baskets, secondary strainers and a removable water trap (fowl air trap).


These accessories are easily removed for cleaning individually and the drain bowl itself.

A summary is adjacent with specific details for all the drain bowl types on the following pages.

**Start here**

Follow the numbers to check if each is needed...


**When ordering:** Each accessory (including the drain bowl) has a separate product number.



Frameless Ladder Grate shown. Fully welded for strength and no places for bacteria to hide.

## 1 Grates

A range of grate types are stocked to suit various load, slip & flow ratings. Options listed page 9.



Standard height Basket (use in a standard height Drain Bowl with or without a FAT).


## 2 Filter Baskets

We stock standard height, extended height and silt baskets with 3mm mesh in accordance with local requirements.

Extended Height Filter Basket (use in standard height Drain Bowl without a FAT).

Dry Silt Trap Basket (use in standard height Drain Bowl without a FAT).

or




FAT with NBR seal ring - removable for easier cleaning.

## 3 Fowl Air Trap (FAT)

This optional accessory creates a water seal but unlike a P-Trap, this can be removed to access the pipework beyond for cleaning.


Use in a standard height Drain Bowl with a standard Filter Basket. Can be used with or without a P-Trap.



2


## Extended Height Baskets

We stock Filter Baskets and Silt Trap Baskets in 'extended' versions for greater capacity, occupying the full height of standard height Drain Bowls.



## 4 Secondary Strainer

Security screw fixed in place above the outlet, this option is a requirement in most local authority approvals.



Concrete levelling and fixing legs standard.

Drain Bowl - Square Top, Standard Height, with vertical 110mm outlet shown.

## 5 Drain Bowl

Hygienic smooth finish design with no laps, cavities or joins & stocked in 316 stainless steel standard.

The 110mm or 160mm spigot outlets connect to a range of drainage pipework including stainless drainage, HDPE and KG2000 PP drainage.

**This guide is only for standard applications.**

For specific or specialised applications please contact us first - [www.auspress.com.au](http://www.auspress.com.au)



### Need WaterMark or Supermarket Approved Spec?


We can help spec with options for leading national supermarkets.

Items with WaterMark approval are notated with a WM in this catalogue.




**200****Drain Bowl 200 Square, Standard Height, 110-V Outlet**

Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.




Ref	Item	Product No	Notes
G	Grate	See 'G2.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB2.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB2.200.03	3mm aperture
SB	Silt Basket (Solid Bottom)	AD.SB2.200.03	3mm aperture
FAT	Removable Foul Air Trap (FAT) <sup>WM</sup>	AD.FAT2.KIT	Flow Rate <sup>‡</sup> : 3.5 L/sec
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
DB	Drain Bowl <sup>WM</sup>	AD.DB2.SQS.110V	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>‡</sup> : 3.5 L/sec

<sup>‡</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.

**200****Drain Bowl 200 Square, Low Height, 110-V Outlet**


Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.



Note: A 'FAT' cannot be used with this drain.

Ref	Item	Product No	Notes
G	Grate	See 'G2.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB2.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB2.200.03	3mm aperture
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
DB	Drain Bowl <sup>WM</sup>	AD.DB2.SQL.110V	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>‡</sup> : 3.5 L/sec

<sup>‡</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.







200

## Drain Bowl 200 Square, Standard Height, 110-H Outlet

Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.




Note: Both a Filter Basket and a 'FAT' must be used with this drain.

Ref	Item	Product No	Notes
G	Grate	See 'G2.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB2.075.03	3mm aperture
FAT	Removable Foul Air Trap (FAT) <sup>WM</sup>	AD.FAT2.KIT	Flow Rate <sup>†</sup> : 3.5 L/sec
DB	Drain Bowl <sup>WM</sup>	AD.DB2.SQS.110H	

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.

### B Installed with Internal Trap



<<< Accessories fit within drain bowl. Each ordered & sold separately.



200

## Drain Bowl 200 Vinyl, Standard Height, 110-V Outlet

Material: 316L stainless steel body, Vinyl lock ring top.  
Top: Round vinyl lock top sheet floor finishes 1.5 - 3mm thick.




Ref	Item	Product No	Notes
G	Grate	See 'G2.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB2.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB2.200.03	3mm aperture
SB	Silt Basket (Solid Bottom)	AD.SB2.200.03	3mm aperture
FAT	Removable Foul Air Trap (FAT) <sup>WM</sup>	AD.FAT2.KIT	Flow Rate <sup>†</sup> : 3.5 L/sec
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
DB	Drain Bowl <sup>WM</sup>	AD.DB2.VLS.110V	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>†</sup> : 3.5 L/sec


<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.

### A Installed with P-Trap

<<< Accessories fit within drain bowl. Each ordered & sold separately.




### B Installed with Internal Trap



**300****Drain Bowl 300 Square, Standard Height, 110-V Outlet**



Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.




Ref	Item	Product No	Notes
G	Grate	See 'G3.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB3.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB3.200.03	3mm aperture
SB	Silt Basket (Solid Bottom)	AD.SB3.200.03	3mm aperture
FAT	Removable Foul Air Trap (FAT) <sup>WM</sup>	AD.FAT3.KIT	Flow Rate <sup>†</sup> : 4.6 L/sec
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
DB	Drain Bowl <sup>WM</sup>	AD.DB3.SQS.110V	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>†</sup> : 3.5 L/sec

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.

<<< Accessories fit within drain bowl. Each ordered & sold separately.

**300****Drain Bowl 300 Square, Standard Height, 160-V Outlet**



Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.



Ref	Item	Product No	Notes
G	Grate	See 'G3.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB3.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB3.200.03	3mm aperture
SB	Silt Basket (Solid Bottom)	AD.SB3.200.03	3mm aperture
FAT	Removable Foul Air Trap (FAT) <sup>WM</sup>	AD.FAT3.KIT	Flow Rate <sup>†</sup> : 4.6 L/sec
SS	Secondary Strainer Kit	AD.SSK.160.03	3mm aperture
DB	Drain Bowl <sup>WM</sup>	AD.DB3.SQS.160V	
PT	P-Trap <sup>WM</sup>	AP.PT.160	Flow Rate <sup>†</sup> : 7.5 L/sec

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.


<<< Accessories fit within drain bowl. Each ordered & sold separately.



300

## Drain Bowl 300 Square, Standard Height, 110-H Outlet

Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.




Note: Both a Standard Filter Basket and a 'FAT' must be used with this drain.

Ref	Item	Product No	Notes
G	Grate	See 'G3.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB3.075.03	3mm aperture
FAT	Removable Foul Air Trap (FAT) <sup>WM</sup>	AD.FAT3.KIT	Flow Rate <sup>†</sup> : 4.6 L/sec
DB	Drain Bowl <sup>WM</sup>	AD.DB3.SQS.110H	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>†</sup> : 3.5 L/sec

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.

### B Installed with Internal Trap


<<< Accessories fit within drain bowl. Each ordered & sold separately.



300

## Drain Bowl 300 Square, Low Height, 110-V Outlet

Material: 316L stainless steel body, epoxy infill hygienic & strong top edge.  
Top: Square top for concrete, tiled or epoxy floor finishes.




Note: The 'FAT' and/or Extended Filter Basket cannot be used with this drain.

Ref	Item	Product No	Notes
G	Grate	See 'G3.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB3.075.03	3mm aperture
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
DB	Drain Bowl <sup>WM</sup>	AD.DB3.SQL.110V	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>†</sup> : 3.6 L/sec

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.

### A Installed with P-Trap


<<< Accessories fit within drain bowl. Each ordered & sold separately.



200



**Drain Bowl 200 Round, Standard Height, 110-V Outlet**

Material: 316L stainless steel body, solid stainless 10mm top edge.  
Top: Round top for concrete or epoxy floor finishes.



Ref	Item	Product No	Notes
G	Grate	See 'G3.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB2.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB2.200.03	3mm aperture
SB	Silt Basket (Solid Bottom)	AD.SB2.200.03	3mm aperture
FAT	Removable Trap (FAT) <sup>WM</sup>	AD.FAT2.KIT	Flow Rate <sup>‡</sup> : 3.6 L/sec
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
<b>DB</b>	<b>Drain Bowl</b> <sup>WM</sup>	<b>AD.DB2.RDS.110V</b>	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>‡</sup> : 3.5 L/sec

<sup>‡</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.




<<< Accessories fit within drain bowl. Each ordered & sold separately.

300



**Drain Bowl 300 Round, Standard Height, 110-V Outlet**

Material: 316L stainless steel body, solid stainless 10mm top edge.  
Top: Round top for concrete or epoxy floor finishes.



Ref	Item	Product No	Notes
G	Grate	See 'G3.SQ' grate options page AD9.	
FB	Filter Basket (Standard)	AD.FB3.075.03	3mm aperture
FBX	Filter Basket (Extended)	AD.FB3.200.03	3mm aperture
SB	Silt Basket (Solid Bottom)	AD.SB3.200.03	3mm aperture
FAT	Removable Trap (FAT) <sup>WM</sup>	AD.FAT3.KIT	Flow Rate <sup>‡</sup> : 4.6 L/sec
SS	Secondary Strainer Kit	AD.SSK.110.03	3mm aperture
<b>DB</b>	<b>Drain Bowl</b> <sup>WM</sup>	<b>AD.DB3.RDS.110V</b>	
PT	P-Trap <sup>WM</sup>	AP.PT.110	Flow Rate <sup>‡</sup> : 3.6 L/sec

<sup>‡</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.  
<sup>WM</sup> Item approved as part of a WaterMark approved assembly.




<<< Accessories fit within drain bowl. Each ordered & sold separately.



**400  
XL**

## Drain Bowl 400 Square, Standard Height, 160-V Outlet

Material: 316L stainless steel body.  
Top: Square top for concrete, tiled or epoxy floor finishes.




Ref	Item	Product No	Notes
G	Grate	See 'G4.SQ' grate options page AD9.	
FBX	Filter Basket (Extended)	AD.FB4.260.03*	
SS	Secondary Strainer Kit	AD.SSK.160.03	3mm aperture
<b>DB</b>	<b>Drain Bowl</b>	<b>AD.DB4.SQS.160V*</b>	Flow Rate <sup>†</sup> : 10.0 L/sec
PT	P-Trap	AP.PT.160	Flow Rate <sup>†</sup> : 7.5 L/sec
45B	45° Bend 160mm	AP.B.45.160	

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.

\* Item available on request, lead time likely.

### A Installed with P-Trap


**600  
XL**


## Drain Bowl 600 Square, Standard Height, 200-V Outlet

Material: 316L stainless steel body.  
Top: Square top for concrete, tiled or epoxy floor finishes.


Ref	Item	Product No	Notes
G	Ladder Grate (568x284mm)	AD.G6.SQ.L12*	2x required per Drain Bowl.
<b>DB</b>	<b>Drain Bowl</b>	<b>AD.DB6.SQS.200V*</b>	Flow Rate <sup>†</sup> : ~60.0 L/sec

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions. Accessories may reduce flow further.

\* Item available on request, lead time likely.



### A High Volume Option








200

**G2.SQ Grate Options**


168x168mm for 200 Square Top Drain Bowls

Style	Load <sup>†</sup>	Product No
FL	12,500	AD.G2.SQ.FL
L	5,000	AD.G2.SQ.L5
L	12,500	AD.G2.SQ.L12 (with anti-tilt)
M	1,500	AD.G2.SQ.M
C	5,000	AD.G2.SQ.C
S	5,000	AD.G2.SQ.S*
W	1,500	AD.G2.SQ.W
GTS	5,000	AD.G2.SQ.GTS
GTP	5,000	AD.G2.SQ.GTP*


\* Item available on request, lead time likely.




**FL** Frameless Ladder Hygiene Grate  
Material: 316 stainless steel.  
Finish: Electropolished.




**L** Ladder Grate (L12 shown)  
Material: 316 stainless steel.  
Finish: Mill finish.




**M** Mesh Grate  
Material: 316 stainless steel.  
Finish: Electropolished.




**C** Cast Hygiene Stainless Grate  
Material: 304 stainless steel.  
Finish: Smooth cast finish.




**S** Slot Grate  
Material: 316 stainless steel.  
Finish: Polished top.



**W** Wedge Wire Grate  
Material: 316 stainless steel.  
Finish: Grip dimples.



**GTS** Gas Tight Screw Cover  
Material: 316 stainless & EPDM edge and base gaskets.  
Finish: Polished top.  
**Note:** Lubricate seal before fitting.  
**Lifting Key to Remove?**  
Order a AD.KEY (sold separately)



**GTP** Gas Tight Plain Cover  
Material: 316 stainless & EPDM edge and base gaskets.  
Finish: Polished top.  
**Note:** Lubricate seal before fitting.

400 XL

**G4.SQ Grate Options**

368x368mm for 400 Square Top Drain Bowls

Style	Load <sup>†</sup>	Product No
L	5,000	AD.G4.SQ.L*
M	1,500	AD.G4.SQ.M*

\* Item available on request, lead time likely.


200

**G2.RD Grate Options**


Ø170mm for 200 Round &amp; Vinyl Lock Drain Bowls

Style	Load <sup>†</sup>	Product No
FL	12,500	AD.G2.RD.FL
C	7,000	AD.G2.RD.C
L	5,000	AD.G2.RD.L5
L	12,500	AD.G2.RD.L12* (with anti-tilt)
M	1,500	AD.G2.RD.M
GTS	5,000	AD.G2.RD.GTS <sup>‡</sup>
GTP	5,000	AD.G2.RD.GTP* <sup>‡</sup>
W	1,500	AD.G2.RD.W


\* Item available on request, lead time likely.

<sup>‡</sup> Item not suitable for vinyl lock drain types.


**FL** Frameless Ladder Hygiene Grate  
Material: 316 stainless steel.  
Finish: Electropolished.




**L** Ladder Grate (L12 shown)  
Material: 316 stainless steel.  
Finish: Mill finish.




**W** Wedge Wire Grate  
Material: 316 stainless steel.  
Finish: Electropolished.



**M** Mesh Grate  
Material: 316 stainless steel.  
Finish: Electropolished.



**GTS** Gas Tight Cover - Screw  
Material: 316 stainless & EPDM.  
Finish: Mill finish.  
**Note:** Lubricate seal before fitting.  
**Lifting Key to Remove?**  
Order a AD.KEY (sold separately)



**GTP** Gas Tight Cover - Plain  
Material: 316 stainless & EPDM.  
Finish: Polished top.  
**Note:** Lubricate seal before fitting.

300

**G3.RD Grate Options**

Ø268mm for 300 Round Drain Bowls

Style	Load <sup>†</sup>	Product No
FL	12,500	AD.G3.RD.FL
C	5,000	AD.G3.RD.C
L	5,000	AD.G3.RD.L5
GTS	5,000	AD.G3.RD.GTS
GTP	5,000	AD.G3.RD.GTP*
M	1,000	AD.G3.RD.M
W	1,500	AD.G3.RD.W*

\* Item available on request, lead time likely.

<sup>†</sup> Load ratings to EN1253 testing in kilograms (kg). Lesser values for solid wheel and moving wheel loads.  
Slip ratings tested to EN13036.

Check the individual drain bowl page for suitability as not all accessories shown fit all drain bowl types.

200

200

200

Items below for '200' Drain Bowls

300

300

Items below for '300' size Drain Bowls

## Filter Basket Options


Material: 316 stainless steel.

### Why Use a Filter Basket?

The mesh of the Filter Basket prevents solids in wash down waters from passing and possibly blocking the drainage beyond so this material can be disposed of appropriately.

### Retaining Chain?

We can fix the basket to the drain bowl to prevent the basket being thrown away.



FB


'Standard' Height Filter Basket



FBX


'Extended' Height Filter Basket

Cannot be used with a Foul Air Trap (FAT).



FB

'Standard' Height Filter Basket



FBX

'Extended' Height Filter Basket

Cannot be used with a Foul Air Trap (FAT).

Mesh	Hole	Product No	Product No
3mm	3.25Ø	AD.FB2.075.03	AD.FB2.200.03
Volume:		0.7 L	2.0 L


Product No	Product No
AD.FB3.075.03	AD.FB3.200.03
1.9 L	6.2 L

## Silt Basket Options

Material: 316 stainless steel.

### Why use a Silt Basket?


When wash down water contains fine or sand like solids, these particles fall to the solid bottom for collection and allow the water to overflow through the mesh and drain beyond.



SB

Dry 'Silt' Basket with Solid Bottom

Cannot be used with a Foul Air Trap (FAT).



SB

Dry 'Silt' Basket with Solid Bottom

Cannot be used with a Foul Air Trap (FAT).

Mesh	Hole	Product No
3mm	3.25Ø	AD.SB2.200.03
Volume:		2.0L

Product No
AD.SB3.200.03
6.2L

## Foul Air Trap (FAT) Removable


Material: 316 stainless steel with NBR seal.

### Why Use A FAT?

With the Fowl Air trap removed, pipework beyond is clear for maintenance access.


Use instead of a P-Trap to reduce the IL depth of the outlet.

**FAT must be used with a standard height Filter Basket in a standard height Drain Bowl (all sold separately).**



FAT

Fowl Air Trap (FAT) with NBR Sealing Ring



FAT

Fowl Air Trap (FAT) with NBR Sealing Ring


Seal Height	Product No
75mm	AD.FAT2.KIT
Flow Rate <sup>†</sup> :	3.5 L/sec

Product No
AD.FAT3.KIT
4.6 L/sec

<sup>†</sup> Max rate based on a continuous flow of water in clean conditions with vertical outlet drain bowl.


## ■ Secondary Strainer Option

Material: 316 stainless steel.



### Strainer (Screw Fixed)

Secured with 3x torx screws to the Drain Bowl outlet. Screw Fixed available on request.



### Strainer (Clip-In)

With 3x support legs, no fixing ring required (not shown).

Outlet OD	Aperture	Style	Product No	Open %
110	3.2mm	SS1	AD.SSK.110.03	42%
160	3.8mm	SS1	AD.SSK.160.03	43%

### Requirements for Trade Waste:

Some Water Authorities list 'Screw Fixed' Secondary Strainers as a standard requirement. Please ask if you're unsure.

Key to remove? Order a **AD.KEY**


## ■ P-Trap Socket - Spigot

Material: 316 stainless steel, mill finish.  
Ring Seal: EPDM x1 fitted.

Riser	Product No	D1	X4
A small vertical length may be required. Riser length sold separately.	AP.P.015.110	110	225
	AP.P.025.160	160	345


P-Trap	Product No	D1	X1	X2	X3	Flow Rate†
	AP.PT.110	110	132	300	254	3.4 L/sec
	AP.PT.160	160	190	403	347	7.5 L/sec

† Max rate based on a continuous flow of water in clean conditions.



## ■ Bend 45° Socket - Spigot

Material: 316 stainless steel, mill finish.  
Ring Seal: EPDM x1 fitted.



Double 45 bend arrangements shown for offset dimensions only - each bend sold separately.


Product No	D1	X1	X5	X6
AP.B.45.110	110	93	195	150
AP.B.45.160	160	131	269	200

## ■ Mini Filter Basket

Material: 316 stainless steel.

### When use the Mini Basket?

With a collection volume of 300mL, the Mini Basket is used when solids are few in washdown water.



'Mini' Filter Basket  
Suitable to selected 110mm spigot outlets.

Suits items with a 110mm spigot outlet.


Mesh	Hole	Product No
3mm	3.25Ø	AD.FB1.075.03

## ■ Clearout (IP Cover)

Material: 316 stainless steel, polished top finish.  
Lid seal: Neoprene gasket.

Polished 316 stainless steel top finish.

Allen head screws fitted standard.  
Security screws are available on request.




Product No	D1	D2	X1
AP.CO.110	110	128	90
AP.CO.160	160	180	100

## ■ Retaining Chain

Material: 316 stainless steel.

A Retaining Chain can be fitted between the Filter Basket and the Drain Bowl to prevent the basket being left out of the Drain Bowl or discarded.



Length	Product No
700mm	AD.RCK.0700*

\* Item available on request, lead time likely.



# Floor Gully Invert Chart



Configurations show the minimum invert level (IL) for each drain bowl type, with P-Trap and 2x 45 Bend scenarios. Fitting dimensions used from the AusPress Stainless Drainage Range, other fitting types may vary.

